

KINGFISHERLP3

- Ultra Low power consumption
- Compatible with virtually any SCADA
- Simple installation
- Modular Communications
- ISaGRAF and all IEC 61131-3 Languages



Ahorre tiempo de ingeniería con una configuración simple.



Acceso instantáneo a datos críticos de sus activos remotos.



Plataforma segura, que protege sus activos y datos.



Minimizar el riesgo de falla del sistema



Incrementar la eficiencia de la red



Para mayor información favor de ponerse en contacto con nosotros.

Tels: 55 4334 - 9242
55 6584 - 9782

ventas@atautomation.com.mx



KINGFISHER LP3

A smart solution for low-power monitoring, control and data logging applications

GENERAL

Input supply	9.0 - 15.0 V DC @2A max
Power consumption, I/O scan	<55 mA (option ports 3 & 4 not loaded)
Power consumption, sleeping	<2 mA via DC supply
Operating temperature range	-20 °C to +70 °C (excluding battery)
Operating humidity	5% to 98% R.H. non condensing
CPU	Hitachi H8S/2144 operating at 32KHz or 7.38MHz
Flash RAM	4Mb
Static CMOS RAM	4K internal, 512K external (battery backed)
Real-time clock	Yes
Battery backup for RAM & RTC	Yes, Lithium
Backup battery lifetime	7 years at 25 °C
Dimensions	185mm (H) x 130mm (W) x 50mm (D)
Comm Port 1	RS-232, 300 to 38,400bps non isolated
Comm Port 2	RS-232/RS-485, 300 to 38,400bps isolated
Comm Port 3 & Comm Port 4	Refer to list of card options below: A4 Ethernet MTRJ Fiber F Serial Fibre H HART I Isolated Serial L Private line 1200 Baud T4 Ethernet

DIGITAL INPUTS

Number of inputs	8 Max. Channels 5 to 8 can be configured as digital outputs
Input voltage range	5 to 30V DC=ON; 0 to 1.0V DC = OFF

DIGITAL OUTPUTS

Number of outputs	2 latching relays, plus up to 4 Open Drain (Channels 5 - 8)
Maximum voltage	Relays 30V AC/DC, Open Drain 30V DC
Maximum switching current	Relays 2A, Open Drain 300mA total
Isolation	500V (relay)

ANALOGUE INPUTS

Number of inputs	4 plus (inc. battery. V, RTU current, RTU temp & ADCV Ref)
Input voltage range	0-5V (0-20mA with ext. 250 Ohm resistance)
A/D converter resolution	12 bit
Binary input range	0 to 32,760

ANALOGUE OUTPUT

Output range	1 x 0-5V, 4-20mA sink
D/A converter resolution	15 bit
Isolation	500V RMS

CERTIFICATIONS INCLUDE

A-Tick	Comms options D, R1 and R2
C-Tick	Main module plus comms options A3, D, I, L, R2, R3, T3

www.ovarro.com

Ovarro has a global network of offices and distributors.
Visit our website to find your local office.

